

SHORT-INFO

# HandyTIG 200

**TIG welding optimised for use on construction sites.**

- ITC-Inside
- Long duty cycle
- Protected against falls from a height of up to 60 cm
- Pulse function: fast pulse up to 2 kHz
- Job memory



## At a glance

### **Intuitive operation**

Offering exceptional ease of use and intuitive operation, the Lorch HandyTIG series allows you to produce unparalleled welding results thanks to its automatic setting control.

### **Non-contacting HF ignition**

The TIG arc is ignited without direct contact by high-voltage pulses. Ignition is triggered with the press of a button to ensure that the tungsten electrode does not come into contact with the workpiece. Putting an end to welds with tungsten inclusions, this technology reduces the strain on the electrode. When working in HF-sensitive environments or on tools, the operator has the additional option of switching to ContacTIG (contact ignition).

### **Automatic gas management**

Automatic gas management is applied to automatically regulate the gas pre-flow and post-flow, thereby protecting electrode and weld pool against oxidation.

### **Connection for hand or foot remote control**

We offer a variety of hand or foot remote controls for the Lorch HandyTIG 200 that allow you to step into the welding process and adjust the welding current if the welding machine happens to be positioned in a place that is not right beside you

### **Changeover DC to AC**

Offering you an effortless way to toggle between DC and AC, the Lorch HandyTIG 200 allows you to remain completely flexible.

### **Pulse and fast pulse up to 2 kHz**

The standard pulse function with up to 2 kHz that is built into every machine offers you additional benefits when welding thin plates.

## Benefits

### Compact and protected against falls

Its compact design and low weight make working with the Lorch HandyTIG 200 an absolute joy. Meanwhile, its exceptionally robust case keeps the machine perfectly safe if subjected to falls from heights of up to 60 cm.

### Electrode welding function

Electrode welding with Hotstart, Anti-Stick and Arc-Force regulation: The automatic Hotstart feature guarantees perfect ignition every time, while the Anti-Stick system reliably prevents the electrode from sticking, and Arc-Force regulation supports the welding process by providing for increased arc stability and optimised metal transfer.

### Intelligent Torch Control

Intelligent Torch Control enables each machine to automatically detect whether the welder uses a standard torch or one of the latest, fully digital Lorch TIG torches including Powermaster remote control.

### Energy-efficient

The Lorch HandyTIG 200 utilises leading-edge industrial electronics and fan-on-demand technology to achieve a superior level of efficiency and exceptionally low power consumption.

### Job memory

The job memory can store up to four welding jobs.

## Controlconcept

### ControlPro

- User-oriented guidance
- Infinitely adjustable welding current setting
- Remote control connection
- Exact-ampere digital display
- Simple setting of the base parameters
- Job memory
- Powermaster torch remote control
- UpDown remote control torch
- Pulse function



**Technical Data: HandyTIG-Serie****Handy 180****HandyTIG 180****HandyTIG 200****TIG**

welding range (in Amps)	5-180	3-180	3-200
current setting	infinitely variable	infinitely variable	infinitely variable

**Electrode**

weldable electrodes (mm)	1,5-3,25	1,5-4,0	1,5-4,0
--------------------------	----------	---------	---------

**Duty cycle TIG DC**

duty cycle 100% (in Amps) - DC	115	130	160
duty cycle 60% (in Amps) - DC	135	150	180
duty cycle at max. current (in %) - DC	40%	30%	45%

**Mains**

mains voltage (in V)	230	230	230
phases (50/60 Hz)	1~	1~	1~
positive mains tolerance (in %)	15%	15%	15%
negative mains tolerance (in %)	25%	25%	25%
mains fuse (in Amps)	16	16	16
mains plug	Schuko	Schuko	Schuko

**Dimensions and weights**

dimensions (LxWxH) (in mm)	337x130x211	337x130x211 / 480x185x326	480x185x326
weight (in kg)	5,7	6,5/13,3	13,4

**Standards and approvals**

standard	EN 60974-01	EN 60974-01	EN 60974-01
protection class (EN 60529)	IP23	IP23	IP23
insulation class	F	F	F
designation	CE, S	CE, S	CE, S

**Duty cycle TIG AC (only AC systems)**

duty cycle 100% (in Amps) - AC	130	160
duty cycle 60% (in Amps) - AC	150	180
duty cycle at max. current (in %) - AC	35%	45%